

1. Identification

Product Code CC7704-16

Product Name **ortho-CRESOL pure**

Molecular Formula $\text{CH}_3\text{C}_6\text{H}_4\text{OH}$ =108.14

CAS Number 95-48-7

Supplier:  **BEECROFT & PARTNERS**
Northfield Road
Rotherham
South Yorkshire

Phone 01709-377881
Fax 01709-369264

Emergency Telephone 08:30-1700 01709-377881
24hr 112
(Have this document to hand)

2. Composition

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
Cresol, all isomers	95-48-7	202-423-8	> 98.0%	T : R24/25,R34	OES

3. Hazards Identification

Toxic in contact with skin and if swallowed. Causes burns.

4. First Aid Measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.

Skin Remove contaminated clothing immediately avoiding contamination of unaffected areas. Swab contaminated skin with a mixture of 70 parts polyethylene glycol and 30 parts alcohol. Alternatively use glycerol or polyethylene glycol, or if solvents are not available flush with water for at least 10 minutes. OBTAIN MEDICAL ATTENTION URGENTLY.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. Convulsions may occur and cause unconsciousness. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

5. Fire Fighting Measures

Hazards Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus. Vapour-air mixtures are explosive.

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

6. Accidental Release Measures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.
Environmental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.
Major Spillage	If molten allow to solidify first. Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

7. Storage & Handling

Handling Precautions	All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing. Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.
Storage Conditions	Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

8.1 Occupational Exposure Limits

Occupational Exposure Standard	Long Term (8hr TWA):	5	ppm	22	mg m-3
	Short Term (15min Period):	-	ppm	-	mg m-3

Special Hazards	Can be absorbed through skin.
-----------------	-------------------------------

8.2 Personal Protection

Respiratory	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hands	Use PVC gauntlets.
Eyes	Use chemical full face shield.
Skin	Wear PVC oversuit.

9. Physical & Chemical Properties

Appearance	White or pale yellow tinted crystals or crystalline powder.
Odour	Distinctive, sweet tarry odour and burning taste.
pH	6 @ 20 °C
Boiling point	191.0 °C
Melting point	32.0 °C
Flash point	81.0 °C (Closed cup)
Upper Flammable Limit	0.0%
Lower Flammable Limit	1.3%
Auto Ignition	715.0 °C
Explosive properties	Moderate/severe in confined spaces.
Oxidising Properties	No.
Vapour Pressure	0.25 mm Hg @25,C
Relative Density	1.0720
Water Solubility	Slightly soluble in water.

10. Stability & Reactivity

Chemical Stability	Stable under normal conditions
Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
Materials to Avoid	Acetaldehyde. Aluminium chloride plus nitro benzene or nitromethane. Sodium nitrite.

10. Stability & Reactivity (continued)

Hazardous None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.
Decomposition Products

11. Toxicological Information

Eyes The solid, molten liquid and solutions are irritating to the eyes. Damage can range from severe irritation and corneal scarring to permanent blindness.

Skin Toxic when absorbed through skin. Contact with the solid or solution will cause burns.

LD50 Skin Rat 620 mg/Kg

Ingest Causes severe corrosion of the mouth, throat and gastro-intestinal tract. Ingestion may prove fatal.

LD50 Ingest Rat 121 mg/Kg

Inhalation Contact with the liquid or vapour will Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes, nose, throat and respiratory tract. High concentrations of vapour may cause digestive and nervous disorders, pulmonary oedema or liver and kidney failure.

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity May be a mutagen.

Reproductive Effects An increased incidence of preimplantation loss and early postnatal deaths have been reported in the offspring of rats exposed to the vapour throughout pregnancy.

12. Ecological

Slightly toxic to aquatic species but will bioaccumulate.

13. Disposal Considerations

Disposal Methods Dispose of in a licensed incinerator. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems.

Contaminated Packaging Clean out with a weak sodium hydroxide solution then wash out thoroughly with water. Use a licensed waste disposer.

14. Transport Information

Proper Shipping Name Cresol, liquid
UN Number 2076
UN Classification 6.1 Toxic
Subsidiary Risk 8 Corrosive
Flash Point 81.0 °C (Closed cup)
Packing Group II
Marine pollutant No
ADR Hazard ID 68




15. Regulatory Information

Labelling Toxic.
Classification

Label Symbols

T



Risk & safety Phrases Toxic in contact with skin and if swallowed. Causes burns. Keep locked up and out of reach of children. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label).

15. Regulatory Information (continued)

EEC Number

202-423-8

16. Other Information

Document Information This document has been prepared in accordance with directive 88/379/EEC.

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment.

Revision Date: 20/11/03.

Data reviewed and PDF file generated: 07/06/04.

Copyright 2004 Beecroft & Partners.