

Product Code	CW4000-24		
Product Name	WHITE SPIRIT		
Other Names	ute		
CAS Number	64742-88-7		
Supplier:	BEECROFT & PARTNERS		
	Northfield Road Rotherham South Yorkshire		
Phone	01709-377881		
Fax	01709-369264		
Emergency Telephone	08:30-1700	01709-377881	
	24hr		112
	(Have this document to hand)		

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
White spirit	64742-88-7	265-191-7	> 99.5%	R10, R65	OES

Flammable. Harmful: may cause lung damage if swallowed.

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. In severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Hazards	Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus. Vapour-air mixtures are explosive.
Extinguishing Media	Water spray, foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

6. Accidental Release Measures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.
Environmental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.
Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

7. Storage & Handling

Handling Precautions	All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing. Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.
Storage Conditions	Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents. Large quantities must be stored in accordance with the Petroleum Spirits Act.

8.1 Occupational Exposure Limits

Occupational Exposure Standard	Long Term (8hr TWA):	100	ppm	575	mg m-3
	Short Term (15min Period):	125	ppm	720	mg m-3

8.2 Personal Protection

Respiratory	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hands	Use solvent resistant gloves.
Eyes	Use chemical splash proof glasses or goggles.
Skin	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

9. Physical & Chemical Properties

Appearance	Clear colourless liquid.
Odour	Characteristic.
pH	Not available
Boiling point	165.0 °C 150-195 C
Melting point	Not available
Flash point	52.0 °C (Closed cup)
Upper Flammable Limit	8.0%
Lower Flammable Limit	0.6%
Auto Ignition	240.0 °C
Explosive properties	Severe in confined spaces.
Oxidising Properties	No.
Vapour Pressure	1.9 mmHg @ 20,C
Relative Density	0.7830
Water Solubility	Insoluble in water.

10. Stability & Reactivity

Chemical Stability	Stable under normal conditions
Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
Materials to Avoid	Strong oxidising agents.

10. Stability & Reactivity (continued)

Hazardous None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.
Decomposition Products

11. Toxicological Information

Eyes Both the vapour and liquid will, act as an eye irritant.

Skin The liquid is mildly irritating to the skin. Repeated or prolonged contact may defat the skin producing irritation and dermatitis.

LD50 Skin Not available

Ingest Ingestion will cause causes damage to stomach and intestinal linings.

LD50 Ingest Not available

Inhalation Exposure to vapour concentrations above the occupational exposure limits will cause narcosis. Prolonged exposure to vapour concentrations above the occupational exposure limits will cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may produce central nervous system depression and unconsciousness.

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects No information is available.

12. Ecological

Expected to be toxic to aquatic life if discharged to natural waters.

13. Disposal Considerations

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

14. Transport Information

Proper Shipping Name Turpentine substitute
UN Number 1300
UN Classification 3 Flammable liquid
Subsidiary Risk None
Flash Point 52.0 °C (Closed cup)
Packing Group III
Marine pollutant No
ADR Hazard ID 30



15. Regulatory Information

Labelling Flammable, Harmful.
Classification

Risk & safety Phrases Flammable. Harmful: may cause lung damage if swallowed. Keep out of reach of children. Do not breath vapour. Avoid contact with skin. If swallowed, do not induce vomiting; seek medical advice immediately and show this label/container.

EEC Number 265-191-7

16. Other Information

Document Information This document has been prepared in accordance with directive 88/379/EEC.

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment.

Revision Date: 19/11/03.

Data reviewed and PDF file generated: 07/06/04.

Copyright 2004 Beecroft & Partners.